

Singletons 90S Whole-Nut Butter Mill

(Internally Texture Adjustable)



Specifications

Nominal dimensions: 390mm (H) x 290mm (W) x 550mm (D) - (without PETG hopper chute)
640mm (H) x 290mm (W) x 575mm (D) - (with PETG hopper chute)

Weight: 45Kg Nett

Electrical Motor: 1.5kW (SF1.15), 4P, IP55, TEFC (Totally Enclosed Fan Cooled), 230VAC, 50Hz, CSCR induction electric motor

Voltage: 230 VAC single-phase

Current: 8.4A

Switch: 16A DPST illuminated rocker switch

Production Capacity: 55-60Kg of butter-stock grade feed-stock ground per hour (feedstock dependent)

Hopper Capacity: 9Kg of nuts (incl. PETG hopper chute)

Duty Cycle: 100%

Warranty: Full one year manufacturer's warranty

Features:

- ✓ Proudly New Zealand made.
- ✓ Food grade, BPA free PETG hopper reservoir.
- ✓ Fully sealed to resist pathogen and insect ingress.
- ✓ Hygienic stainless steel end cap outlet cover.
- ✓ Precision machined, durable, hygienic solid stainless steel grinder plates and feed screw for reliable operation and durability.
- ✓ Robust TEFC (totally enclosed fan cooled) motor for continuous duty cycle.
- ✓ Externally accessible motor protecting thermal overload switch.
- ✓ Standard duty electrical switch-gear.
- ✓ IEC type heavy duty 3.0m power cord with integrated 10A plug.
- ✓ Spacer kit supplied to adjust to nominated product texture.
- ✓ Ergonomically designed to be striking yet simple to use and clean.
- ✓ Can be supplied in most standard polyester powder-coat colours.
- ✓ Currently manufacture to comply with AS/NZS 3820:2009 electrical safety standards.
- ✓ Electromagnetic Compatibility Compliance to AS/NZS CISPR 14.1:2010 (CISPR 14-1, Ed 5.1, 2009).
- ✓ Pictorial instruction manual and cleaning disassembly tools included.
- ✓ Optional Residual Current Device type safety plug for added user protection.
- ✓ Optional Feed Jar filler kit to facilitate void free bottling directly into the jar.